



NUBUCK CHIC

— ENTWINE —

ELITE
H O M E W E A R



ELITE
H O M E W E A R

NUBUCK CHIC

Composition: 100% polyester

Weight: 330 gsm

Width: 140 cm

TECHNICAL DETAILS

Abrasion resistance: (BS EN ISO 12947-2/BS EN 14465: 2003 Annex a): >30,000 rubs

Change in shade @ 3000 revs: grade 4

Colour fastness to rubbing (dry):BS EN ISO 105 x 12: 2002: 4-5

Colour fastness to rubbing (wet):BS EN ISO 105 x 12: 2002: 3-4

Colour fastness to light std 5:BS EN ISO 105 b02: 1999:5

Abrasion Resistance (ASTM D4966-2016) : > 50,000 revs

Wyzenbeek Abrasion (ASTM D4157): >51,000 Double Rubs

Martindale Pilling (ASTM D4970): Grade 4.5

Breaking (Tensile) Strength (ASTM D5034): Warp 97.9, Fill 218.5

Seam slippage (ASTM D 4034-92) : Pass

Seam Slippage –BS EN ISO 13936-2:2004: 4

Tear Strength Tongue Method (ASTM D2261): Warp 16.3, Weft 11.8

Color Fastness to Wet /Dry Crocking (AATCC 8): Wet 4.5, Dry 4.5

Flame Retardant cigarette ignition resistance (NFPA 260 standard): PASS class 1

Smolder Resistance of Materials used in Upholstered Furniture (CA TB 117:2013): pass

CARE INSTRUCTIONS



Usage: Upholstery, Cushions.



7



17



37



27



47



4



14



44



67



57



30



50



11



1



70